

**iQ300**  
**iQ 300**  
**Chimney hood**  
**LC77WA532B stainless steel**



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 690 m3/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

#### Features

##### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 582-864/582-974  
 Height of product, without chimney (mm) : 90  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 17.0  
 Type of control : Electronic  
 Number of speed settings : 3  
 Maximum output air extraction (m3/h) : 430  
 Boost position output recirculating (m3/h) : 360  
 Maximum output recirculating air (m3/h) : 300  
 Boost position air extraction (m3/h) : 680  
 Number of lights : 2  
 Noise level (dB(A) re 1 pW) : 58  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable synthetic  
 Connection Rating (W) : 136  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation typology : Wall-mounted



4 242003 651308

#### Optional accessories

LZ50761	Backboard 70 x 72 cm
LZ53250	Recirculating kit

iQ300  
iQ 300  
Chimney hood  
LC77WA532B stainless steel

#### Features

##### Design

- 70 cm wide
- Soft touch button control for extractor speeds and light
- Slimline canopy design
- Height adjustable chimney sections
- For wall mounted installation
- For installation into the base of a wall cupboard
- 70 cm Chimney hood

##### Key features

- Electronic control
- Electronic power level display
- LED lights
- 2 x metal grease filter cassettes
- Steel filter cover
- Soft touch button control with illuminated buttons

##### Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 440 m<sup>3</sup>/h  
Intensive 690 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at  
maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB  
(A) re 20 µPa sound pressure)
- 3 x power levels plus intensive setting
- Automatic intensive revert
- Adjustable automatic after running

iQ300  
iQ 300  
Chimney hood  
LC77WA532B stainless steel

Dimensioned drawings

